

6929 N. Lakewood Avenue Tulsa, OK 74117

PUBLIC NOTICE OF NETWORK CHANGE UNDER RULE 51.329(a)

October 23, 2017

Carrier: Verizon New York Inc., 140 West Street, New York, NY 10007

Contact: For additional information on these planned network changes, please contact:

Harvey Salzberg Global Engineering and System Performance Verizon Wireline Network Operations 140 West Street, 5th Floor New York, NY 10007 212-519-4852

Quadre Washington Manager – Global Engineering and System Performance Verizon Wireline Network Operations 99 Shawan Rd & York Rd, 05 Floor Room 5w17a, Cockeysville, MD 21030 410-856-2512

Implementation Date: On or after May 5, 2018

Planned Network Change(s) will occur at the following locations in New York:

Verizon Central Office	Address	CLLI
NEW DORP 5ESS Switch	42 New Dorp Lane, Staten Island, NY 10306	NYCRNYNDDS0
WILLIAMSBURG C20 Switch	55 Meserole Street, Brooklyn, NY 11206	NYCKNYWMPS1

This notice may also be viewed at http://www.verizon.com/about/terms-conditions/network-disclosures

PLEASE NOTE:

- All references to the New Dorp NY 5ESS switch are associated with CLLI code NYCRNYNDDS0 and will not be repeated throughout this notice.
- All references to the Williamsburg NY C20 switch are associated with CLLI code NYCKNYWMPS1 and will not be repeated throughout this notice.

Description of the Planned Network Change(s):

The Verizon New Dorp 5ESS switch, located at 42 New Dorp Lane, Staten Island, NY 10306, will be retired and removed from the network after all traffic served by this switch is migrated to the Verizon Williamsburg C20 switch located at 55 Meserole Street, Brooklyn, NY 11206. All traffic to be migrated includes, but is not limited to, Inter-LATA (ACCESS/FG-B-D/CLEC/IXC), wireless, and paging traffic.

Description of Reasonably Foreseeable Impact(s) of the Planned Change(s):

Competitive local exchange carriers (CLECs), interexchange carriers (IXCs, IECs), wireless carriers, and paging carriers will need to secure new trunk groups built to the Williamsburg C20 switch or have existing trunk groups to that switch augmented. Carriers that are code holders for access connectivity in the New Dorp switch will be required to reposition the codes to the Williamsburg C20 switch.

All ASRs for the Williamsburg C20 switch must be received no later than March 26, 2018 in order to provide sufficient time to migrate the traffic described above. These direct end office trunk (DEOT) interconnections will support traffic migration for the New Dorp 5ESS switch prior to its eventual decommissioning. Local Exchange Routing Guide (LERG) change effective dates will be posted; prior to decommissioning of the New Dorp 5ESS switch (**on or after May 5, 2018**). This will serve to guide interconnect re-routes of traffic for the six (6) native codes currently served by the New Dorp 5ESS switch to reflect the Williamsburg C20 switch as the new home switch. All ASRs for the Williamsburg C20 switch must carry the project code of **NYCRNYNDDS0**.