



6929 N. Lakewood Avenue
Tulsa, OK 74117

PUBLIC NOTICE OF NETWORK CHANGE UNDER RULE 51.329(a)

November 19, 2019

Carrier: Verizon New Jersey Inc., One Verizon Way, Basking Ridge, NJ 07920

Contact: For additional information on these planned network changes, please contact:

Lisa Thompson
Global Data Network Engineering
Verizon Wireline Network Operations
13100 Columbia Pike, Floor 5 Room 505
Silver Spring, MD 20904
443-862-0212

John Dunne
Senior Manager – Global Data Network Engineering
Verizon Wireline Network Operations
2147 Route 27
Edison, NJ 08817
732-593-4003

Implementation Date: On or after June 1, 2020

Planned Network Change(s) will occur at the following locations in New Jersey:

Verizon Central Office	Address	CLLI
GLASSBORO NJ 5ESS Switch	5 Focer Street, Glassboro NJ 08028	GLBONJGBDS5
CAMDEN NJ CS2K Switch	12 N 7th Street, Camden NJ 08102	CMDNNJCEPS0

This notice may also be viewed at <http://www.verizon.com/about/terms-conditions/network-disclosures>

PLEASE NOTE:

- All references to the Glassboro NJ 5ESS switch are associated with CLI code GLBONJGBDS5 and will not be repeated throughout this notice.
- All references to the Camden NJ CS2K switch are associated with CLI code CMDNNJCEPS0 and will not be repeated throughout this notice.

Description of the Planned Network Change(s):

The Verizon Glassboro NJ 5ESS switch located at 5 Focer Street, Glassboro, NJ 08028, will be retired and removed from the network after all traffic served by this switch is migrated to the Verizon Camden NJ CS2K switch located at 12 N. 7th Street, Camden, NJ 08102. All traffic to be migrated includes, but is not limited to, Inter-LATA (ACCESS/FG-B-D/CLEC/IXC), wireless, and paging traffic.

Description of Reasonably Foreseeable Impact(s) of the Planned Change(s):

Competitive local exchange carriers (CLECs), interexchange carriers (IXCs, IECs), wireless carriers, and paging carriers, will need to secure new trunk groups built to the Camden NJ CS2K switch or have existing trunk groups to that switch augmented. Carriers that are code holders for access connectivity in the Glassboro NJ 5ESS switch will be required to reposition the codes to the Camden NJ CS2K switch.

All ASRs for the Camden NJ CS2K switch must be received no later than May 1, 2020 in order to provide sufficient time to migrate the traffic described above. These direct end office trunk (DEOT) interconnections will support traffic migration for the Glassboro NJ 5ESS switch prior to its eventual decommissioning. Local Exchange Routing Guide (LERG) change effective dates will be posted prior to decommissioning of the Glassboro NJ 5ESS switch (**on or after June 1, 2020**). This will serve to guide interconnect re-routes of traffic for the eight (8) native codes currently served by the Glassboro NJ 5ESS switch to reflect the Camden NJ CS2K switch as the new home switch. All ASRs for the Camden CS2K switch must carry the project code of **GLBONJGBRP0**.